

P/N NAS6306U30D

Description

Fastener Length: 2-11/32", Thread: 3/8-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6306U30D

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-346-9548

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6306U30D Specifications

3a
Right-hand
0.429 Inches Minimum And 0.479 Inches Maximum
2.314 Inches Minimum And 2.344 Inches Maximum
Dished Hexagon
0.188 Inches Minimum And 0.203 Inches Maximum
0.554 Inches Minimum And 0.564 Inches Maximum
0.3735 Inches Minimum And 0.3745 Inches Maximum
0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
0.375 Inches
1.865 Inches Minimum And 1.885 Inches Maximum
24
160000 Pounds Per Square Inch
2.121 Inches Minimum First Hole And 2.167 Inches Maximum First Hole
32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response Overall
Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6306U30D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.