

Description

Fastener Length: 1-1/32", Thread: 3/8-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6306U9
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-500-1723
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6306U9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.429 Inches Minimum And 0.479 Inches Maximum
Fastener Length:	1.001 Inches Minimum And 1.031 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6306 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.