

P/N NAS6307U22D

Description

Fastener Length: 1-29/32", Thread: 7/16-20, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6307U22D

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-019-2444

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6307U22D Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.503 Inches Minimum And 0.553 Inches Maximum |
| Fastener Length: | 1.888 Inches Minimum And 1.918 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.219 Inches Minimum And 0.234 Inches Maximum |
| Width Between Flats: | 0.679 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.4365 Inches Minimum And 0.4370 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.679 Inches Minimum First Hole And 1.729 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6307 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6307U22D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6307U22D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6307U22D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6307U22D and selecting the quantity you want then click "add to cart".