

## P/N NAS632-45

### **Description**

Fastener Length: 3-13/16", Thread: 3/4-16, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS63245

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-063-5006

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS632-45 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.968 Inches Minimum And 1.018 Inches Maximum
Fastener Length:	3.790 Inches Minimum And 3.820 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.701 Inches Minimum And 0.721 Inches Maximum
Width Between Flats:	0.808 Inches Minimum And 0.817 Inches Maximum
Extended Washer Diameter:	1.220 Inches Minimum And 1.230 Inches Maximum
Extended Washer Thickness:	0.168 Inches Minimum And 0.188 Inches Maximum
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.802 Inches Minimum And 2.822 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas632 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS632-45">https://military-fasteners.com/bolts/machine+bolts/NAS632-45</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS632-45">https://military-fasteners.com/bolts/machine+bolts/NAS632-45</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS632-45">https://military-fasteners.com/bolts/machine+bolts/NAS632-45</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS632-45">https://military-fasteners.com/bolts/machine+bolts/NAS632-45</a> and selecting the quantity you want then click "add to cart".