



Military-Fasteners.com

P/N NAS632-48

Description

Fastener Length: 3-63/64", Thread: 3/4-16, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS63248
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-280-5730
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS632-48 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.968 Inches Minimum And 1.018 Inches Maximum
Fastener Length:	3.978 Inches Minimum And 4.008 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.701 Inches Minimum And 0.721 Inches Maximum
Width Between Flats:	0.808 Inches Minimum And 0.817 Inches Maximum
Extended Washer Diameter:	1.220 Inches Minimum And 1.230 Inches Maximum
Extended Washer Thickness:	0.168 Inches Minimum And 0.188 Inches Maximum
Grip Diameter:	0.748 Inches Minimum And 0.749 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.990 Inches Minimum And 3.010 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas632 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS632-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.