

Description

NAS6403U8 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6403U8
Minimum Qty (MOQ):	20
NSN:	5306-00-536-5254
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS6403U8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.298 Inches Minimum And 0.348 Inches Maximum
Fastener Length:	0.808 Inches Minimum And 0.838 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6403 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6403U8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.