

## P/N NAS6404-15

### **Description**

Fastener Length: 1-5/16", Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS640415

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-064-8783

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6404-15 Specifications

Thread Class:	3a
Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Fastener Length:	1.293 Inches Minimum And 1.323 Inches Maximum
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6404-15">https://military-fasteners.com/bolts/shear+bolts/NAS6404-15</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6404-15">https://military-fasteners.com/bolts/shear+bolts/NAS6404-15</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6404-15">https://military-fasteners.com/bolts/shear+bolts/NAS6404-15</a> and selecting the quantity you want then click "add to cart".