

Description

Fastener Length: 1-5/16", Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS640415 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-064-8783 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS6404-15 Specifications

| | |
|-----------------------------|---|
| Thread Class: | 3a |
| Thread Length: | 0.345 Inches Minimum And 0.395 Inches Maximum |
| Fastener Length: | 1.293 Inches Minimum And 1.323 Inches Maximum |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Grip Length: | 0.928 Inches Minimum And 0.948 Inches Maximum |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6404-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.