

Description

Fastener Length: 2-5/16", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS640431
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-507-6638
Schedule B:	8108.90.3060
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS6404-31 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.365 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	2.293 Inches Minimum And 2.323 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.248 Inches Minimum And 0.249 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.928 Inches Minimum And 1.948 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6404 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6404-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.