

**Description**

Fastener Length: 11/16", Thread: 1/4-28, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS64045D                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-334-1309                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS6404-5D Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Thread Length:</b>   | 0.370 Inches Nominal   |
| <b>Fastener Length:</b>   | 0.667 Inches Minimum And 0.697 Inches Maximum  |
| <b>Head Style:</b>  | Dished Hexagon   |
| <b>Head Height:</b>   | 0.125 Inches Minimum And 0.140 Inches Maximum  |
| <b>Width Between Flats:</b>   | 0.429 Inches Minimum And 0.439 Inches Maximum  |
| <b>Grip Diameter:</b>   | 0.2485 Inches Minimum And 0.2495 Inches Maximum  |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole                                    |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches   |
| <b>Grip Length:</b>   | 0.302 Inches Minimum And 0.322 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>  | 28   |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.487 Inches Minimum First Hole And 0.537 Inches Maximum First Hole                                    |
| <b>Material:</b>  | Titanium Alloy Uns R56400 Overall  |
| <b>Material Document And Classification:</b>                            | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>   | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>  | Unjf   |
| <b>Specification/standard Data:</b>                                     | 80205-nas6404 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6404-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.