

P/N NAS6404A5

Description

Fastener Length: 11/16", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6404A5

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-319-2113

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6404A5 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Minimum And 0.395 Inches Maximum |
| Fastener Length: | 0.667 Inches Minimum And 0.697 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Nas 4006 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6404 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6404A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.