

Description

Fastener Length: 11/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6404A5H |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-338-2821 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6404A5H Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Minimum And 0.395 Inches Maximum |
| Fastener Length: | 0.667 Inches Minimum And 0.697 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Hole Diameter: | 0.046 Inches Minimum And 0.056 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Corners |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Nas 4006 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6404 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6404A5H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.