

Description

Fastener Length: 1-13/16", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS6404U23 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-00-500-1446 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS6404U23 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Minimum And 0.395 Inches Maximum |
| Fastener Length: | 1.793 Inches Minimum And 1.823 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.428 Inches Minimum And 1.448 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6404 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6404U23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.