

# P/N NAS6404U37

### **Description**

Fastener Length: 2-5/8", Thread: 1/4-28, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS6404U37
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-498-6711
Schedule B:	8108.90.3060
ECCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6404U37 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Fastener Length:	2.683 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
End Item Identification:	F-22 Raptor
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.313 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6404U37">https://military-fasteners.com/bolts/shear+bolts/NAS6404U37</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.