

Description

Fastener Length: 11/16", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6404U5D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-189-0060
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6404U5D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Fastener Length:	0.667 Inches Minimum And 0.697 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6404 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6404U5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.