

Description

Fastener Length: 1-37/64", Thread: 5/16-2, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6405U18D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-189-0077
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6405U18D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.548 Inches Minimum And 1.578 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	2
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.376 Inches Minimum First Hole And 1.386 Inches Maximum First Hole
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6405 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6405U18D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.