

Description

Length: 2-3/16", Thread: 1/4-24, Thread Length: 7/16", titanium alloy, NAS6405 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6405U29D |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-01-509-5759 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6405U29D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 2.188 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Nominal |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.311 Inches Nominal |
| Shank Unthreaded Hole Diameter: | 0.081 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.812 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.182 Inches Nominal First Hole |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4928 Assn Std 1st Material Response Overall Or Ams4967 Assn Std 2nd Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6405U29D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.