

Description

Fastener Length: 41/64", Hole Diameter: 5/64", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6405U3H |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-188-8362 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6405U3H Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 0.611 Inches Minimum And 0.641 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Hole Diameter: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Grip Diameter: | 0.3115 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.3125 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Corners |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6405 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6405U3H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.