

**Description**

Fastener Length: 3/4", Thread: 5/16-24, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS6405U5                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-188-8369                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6405U5 Specifications

|                                              |                                                                                                        |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                                                                     |
| <b>Thread Direction:</b>                     | Right-hand                                                                                             |
| <b>Thread Length:</b>                        | 0.438 Inches Nominal                                                                                   |
| <b>Fastener Length:</b>                      | 0.745 Inches Minimum And 0.765 Inches Maximum                                                          |
| <b>Head Style:</b>                           | Dished Hexagon                                                                                         |
| <b>Head Height:</b>                          | 0.156 Inches Minimum And 0.171 Inches Maximum                                                          |
| <b>Width Between Flats:</b>                  | 0.492 Inches Minimum And 0.502 Inches Maximum                                                          |
| <b>Grip Diameter:</b>                        | 0.3115 Inches Minimum And 0.3120 Inches Maximum                                                        |
| <b>Nominal Thread Diameter:</b>              | 0.3125 Inches                                                                                          |
| <b>Grip Length:</b>                          | 0.302 Inches Minimum And 0.322 Inches Maximum                                                          |
| <b>Thread Quantity Per Inch:</b>             | 24                                                                                                     |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                                                          |
| <b>Material:</b>                             | Titanium Alloy Overall                                                                                 |
| <b>Material Document And Classification:</b> | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf                                                                                                   |
| <b>Specification/standard Data:</b>          | 80205-nas6405 Professional/industrial Association Standard                                             |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6405U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.