

Description

Fastener Length: 23/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6406PU4 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-360-4823 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6406PU4 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.454 Inches Nominal |
| Fastener Length: | 0.689 Inches Minimum And 0.719 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Locking Feature: | Patch Threads |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.270 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads |
| Material: | Plastic Locking Featuretitanium Alloy Uns R56400 Fastener |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Fastener Or Ams 4967 Assn Std Single Material Response Fastener |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6406 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6406PU4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.