

Description

Fastener Length: 1-25/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6406U21D |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-188-8387 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6406U21D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.454 Inches Nominal |
| Fastener Length: | 1.751 Inches Minimum And 1.781 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3740 Inches Minimum And 0.3745 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.3750 Inches |
| Grip Length: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.578 Inches Minimum First Hole And 1.588 Inches Maximum First Hole |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6406 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6406U21D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.