

**Description**

Fastener Length: 2-1/32", Thread: 3/8-24, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6406U25
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-370-9077
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS6406U25 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.454 Inches Nominal
<b>Fastener Length:</b>	2.001 Inches Minimum And 2.031 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.554 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.374 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.552 Inches Minimum And 1.572 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	95000 Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6406U25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.