

Description

Fastener Length: 21/32", Hole Diameter: 5/64", Thread: 3/8-24, Thread Length: 29/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6406U3H
Minimum Qty (MOQ):	5
NSN:	5306-01-188-8391
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6406U3H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	0.627 Inches Minimum And 0.657 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.3750 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6406 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6406U3H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.