

**Description**

Fastener Length: 2-31/32", Thread: 3/8-24, Thread Length: 29/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6406U40                                |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-01-368-2543                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6406U40 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.454 Inches Nominal  |
| <b>Fastener Length:</b>                      | 2.939 Inches Minimum And 2.969 Inches Maximum   |
| <b>Head Style:</b>                           | Dished Hexagon  |
| <b>Head Height:</b>                          | 0.188 Inches Minimum And 0.203 Inches Maximum   |
| <b>Width Between Flats:</b>                  | 0.554 Inches Minimum And 0.564 Inches Maximum   |
| <b>Grip Diameter:</b>                        | 0.3740 Inches Minimum And 0.3745 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>              | 0.375 Inches  |
| <b>Grip Length:</b>                          | 2.490 Inches Minimum And 2.510 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip   |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall   |
| <b>Material Document And Classification:</b> | Ams 4928 Assn Std Single Material Response Overall And Ams 4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |
| <b>Specification/standard Data:</b>          | 80205-nas6406 Professional/industrial Association Standard  |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6406U40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.