

P/N NAS6407U14

Description

Fastener Length: 1-3/8", Thread: 7/16-20, Thread Length: 1/2", hexagon head, fine thread, NAS6407 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6407U14

Minimum Qty (MOQ):

NSN: 5306-01-490-1708

Schedule B: 8108.90.8000

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS6407U14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	1.403 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.437 Inches Nominal
End Item Identification:	F-22 Raptor
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.875 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6407U14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.