

Description

Fastener Length: 1-23/32", Thread: 7/16-20, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6407U19 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-456-0258 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS6407U19 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.528 Inches Nominal |
| Fastener Length: | 1.701 Inches Minimum And 1.731 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.219 Inches Minimum And 0.234 Inches Maximum |
| Width Between Flats: | 0.678 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.4365 Inches Minimum And 0.4370 Inches Maximum |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 1.178 Inches Minimum And 1.198 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6407 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6407U19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.