

Description

Fastener Length: 1-23/32", Thread: 7/16-20, Thread Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6407U19D
Minimum Qty (MOQ):	1
NSN:	5306-01-355-0979
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6407U19D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	1.701 Inches Minimum And 1.731 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4365 Inches Minimum And 0.4370 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.517 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6407 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6407U19D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.