

## P/N NAS6407U24

### **Description**

Fastener Length: 2", Thread: 7/16-20, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS6407U24
Minimum Qty (MOQ):	5
NSN:	5306-01-488-2312
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6407U24 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	2.028 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.437 Inches Nominal
End Item Identification:	F-22 Raptor
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.500 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6407U24">https://military-fasteners.com/bolts/shear+bolts/NAS6407U24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.