

**Description**

Fastener Length: 1-29/32", Thread: 1/2-20, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6408U22
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-338-3993
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS6408U22 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.503 Inches Minimum And 0.553 Inches Maximum
<b>Fastener Length:</b>	1.888 Inches Minimum And 1.918 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4990 Inches Minimum And 0.4995 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	1.365 Inches Minimum And 1.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6408 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6408U22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.