



Military-Fasteners.com

P/N NAS6408U29

Description

Fastener Length: 2-5/16", Thread: 1/2-20, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6408U29
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-492-5809
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6408U29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	2.340 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.750 Inches Nominal
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
End Item Identification:	F-22
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.812 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6408U29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.