

Description

Fastener Length: 2-47/64", Thread: 1/2-18, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6409U34D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-355-0983
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6409U34D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.550 Inches Minimum And 0.555 Inches Maximum
Fastener Length:	2.704 Inches Minimum And 2.734 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.289 Inches Minimum And 0.296 Inches Maximum
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.5610 Inches Minimum And 0.5615 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
Nominal Thread Diameter:	0.562 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.487 Inches Minimum First Hole And 2.537 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4828 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6409 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6409U34D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.