

Description

Fastener Length: 2-29/64", Thread: 5/8-18, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6410U29D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-395-8751
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6410U29D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Nominal
Fastener Length:	2.423 Inches Minimum And 2.453 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Grip Diameter:	0.6235 Inches Minimum And 0.6240 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum Grip And 0.151 Inches Maximum Grip
Nominal Thread Diameter:	0.625 Inches
Grip Length:	1.802 Inches Minimum And 1.822 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.216 Inches Minimum Grip And 2.256 Inches Maximum Grip
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6410 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6410U29D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.