



Military-Fasteners.com

P/N NAS6412U24D

Description

Fastener Length: 2-5/32", Thread: 3/4-16, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6412U24D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-421-6168
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS6412U24D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.666 Inches Nominal
Fastener Length:	2.166 Inches Nominal
Head Style:	Hexagon
Head Height:	0.375 Inches Minimum And 0.390 Inches Maximum
Width Between Flats:	1.058 Inches Nominal
Grip Diameter:	0.748 Inches Minimum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.500 Inches Nominal
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Special Features:	Drilled Shank
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6412U24D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.