

Description

Fastener Length: 4-3/64", Thread: 3/4-16, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6412U36
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-466-4088
Schedule B:	8108.90.3060
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6412U36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.666 Inches Nominal
Fastener Length:	4.026 Inches Minimum And 4.056 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.375 Inches Minimum And 0.390 Inches Maximum
Width Between Flats:	1.052 Inches Minimum And 1.065 Inches Maximum
Grip Diameter:	0.7485 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	3.365 Inches Minimum And 3.385 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std 1st Material Response Overall Or Ams 4967 Assn Std 2nd Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6412U36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.