

**Description**

Fastener Length: 4-3/64", Thread: 3/4-16, Thread Length: 21/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6412U36
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-466-4088
Schedule B:	8108.90.3060
ECCN:	9A991



## P/N NAS6412U36 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.666 Inches Nominal
<b>Fastener Length:</b>	4.026 Inches Minimum And 4.056 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.375 Inches Minimum And 0.390 Inches Maximum
<b>Width Between Flats:</b>	1.052 Inches Minimum And 1.065 Inches Maximum
<b>Grip Diameter:</b>	0.7485 Inches Minimum And 0.7490 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	3.365 Inches Minimum And 3.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,hex Head,close Tolerance
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std 1st Material Response Overall Or Ams 4967 Assn Std 2nd Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6412U36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.