

**Description**

Fastener Length: 1-1/16", Thread: 10-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS653V13                                 |
| Minimum Qty (MOQ):      | 1                                         |
| NSN:                    | 5306-00-808-3798                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS653V13 Specifications

|                                              |                                                          |
|----------------------------------------------|----------------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                       |
| <b>Thread Direction:</b>                     | Right-hand                                               |
| <b>Thread Length:</b>                        | 0.276 Inches Minimum                                     |
| <b>Fastener Length:</b>                      | 1.088 Inches Nominal                                     |
| <b>Head Style:</b>                           | Hexagon                                                  |
| <b>Head Height:</b>                          | 0.110 Inches Nominal                                     |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum            |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum          |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches                                             |
| <b>Grip Length:</b>                          | 0.812 Inches Nominal                                     |
| <b>Thread Quantity Per Inch:</b>             | 32                                                       |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                            |
| <b>Material:</b>                             | Titanium Alloy Uns R54520 Overall                        |
| <b>Material Document And Classification:</b> | Nas 621,6al-4v Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unf                                                      |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS653V13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.