



Military-Fasteners.com

P/N NAS653V14

## Description

Fastener Length: 1-5/32", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS653V14
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-685-2758
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS653V14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.276 Inches Minimum
<b>Fastener Length:</b>	1.136 Inches Minimum And 1.166 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.110 Inches Minimum And 0.125 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Material Document And Classification:</b>	Nas 621,6al-4v Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS653V14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.