

**Description**

Fastener Length: 3/8", Thread: 10-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS653V2
Minimum Qty (MOQ):	5
NSN:	5306-00-685-2772
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS653V2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.276 Inches Minimum
<b>Fastener Length:</b>	0.401 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.110 Inches Nominal
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.125 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Surface Finish:</b>	16.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas621 Alloy 6a1-4v Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas653 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS653V2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.