



Military-Fasteners.com

P/N NAS654V10

Description

Fastener Length: 15/16", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS654V10
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-838-0016
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N NAS654V10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.316 Inches Minimum
Fastener Length:	0.941 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.625 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas 621,6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.