

Description

Fastener Length: 1-9/64", Thread: 1/4-28, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS654V13
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-807-6330
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS654V13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.291 Inches Minimum And 0.341 Inches Maximum
Fastener Length:	1.113 Inches Minimum And 1.143 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas654 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.