

**Description**

Fastener Length: 1-17/64", Thread: 1/4-28, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS654V15D                           |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5306-00-443-6776                     |
| Schedule B:             | 7318.15.8085                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS654V15D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.291 Inches Minimum And 0.341 Inches Maximum                       |
| <b>Fastener Length:</b>   | 1.239 Inches Minimum And 1.269 Inches Maximum                       |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.125 Inches Minimum And 0.140 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.2490 Inches Minimum And 0.2495 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches  |
| <b>Grip Length:</b>   | 0.938 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>  | 28  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.111 Inches Minimum First Hole And 1.161 Inches Maximum First Hole |
| <b>Material:</b>  | Titanium Alloy Uns R54520 Overall                                   |
| <b>Material Document And Classification:</b>                            | Nas 621,6al-4v Assn Std Single Material Response Overall            |
| <b>Thread Series Designator:</b>  | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.