

Description

Fastener Length: 2-3/8", Thread: 1/4-28, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS654V33
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-253-3705
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS654V33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.296 Inches Minimum And 0.336 Inches Maximum
Fastener Length:	2.368 Inches Minimum And 2.388 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.052 Inches Minimum And 2.072 Inches Maximum
Thread Quantity Per Inch:	28
Surface Finish:	16.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas654 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.