

Description

Fastener Length: 2-3/16", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS654V35
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-456-5653
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS654V35 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.316 Inches Nominal
Fastener Length:	2.188 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
End Item Identification:	F-15s
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.862 Inches Minimum And 1.882 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,shear
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.