

Description

Fastener Length: 37/64", Thread: 1/4-28, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS654V4D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-283-7472 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS654V4D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.291 Inches Minimum And 0.341 Inches Maximum |
| Fastener Length: | 0.551 Inches Minimum And 0.581 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.423 Inches Minimum First Hole And 0.473 Inches Maximum First Hole |
| Surface Finish: | 16.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas654 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.