

**Description**

Fastener Length: 3-61/64", Thread: 1/4-28, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS654V58D                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-478-6425                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

# P/N NAS654V58D Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Left-hand  |
| <b>Thread Length:</b>   | 0.316 Inches Nominal   |
| <b>Fastener Length:</b>   | 3.926 Inches Minimum And 3.956 Inches Maximum                          |
| <b>Head Style:</b>  | Hexagon  |
| <b>Head Height:</b>   | 0.125 Inches Nominal   |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                          |
| <b>Grip Diameter:</b>   | 0.2490 Inches Minimum And 0.2495 Inches Maximum                        |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole    |
| <b>End Item Identification:</b>   | F18 E/f  |
| <b>Nominal Thread Diameter:</b>   | 0.2500 Inches  |
| <b>Grip Length:</b>   | 3.615 Inches Minimum And 3.635 Inches Maximum                          |
| <b>Thread Quantity Per Inch:</b>  | 28   |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch  |
| <b>Criticality Code Justification:</b>                                  | Agav   |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 3.798 Inches Minimum First Hole And 3.848 Inches Maximum First Hole    |
| <b>Part Name Assigned By Controlling Agency:</b>                        | Bolt,close Tolerance, Hexagon Head,titanium,short Thread, .190 To .500 |
| <b>Material:</b>  | Titanium Alloy Overall   |
| <b>Material Document And Classification:</b>                            | Ams4928 Comp 6al-4v Assn Std Single Material Response Overall          |
| <b>Thread Series Designator:</b>  | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V58D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.