

Description

Fastener Length: 3-61/64", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS654V58D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-478-6425
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS654V58D Specifications

Thread Class:	3a
Thread Direction:	Left-hand
Thread Length:	0.316 Inches Nominal
Fastener Length:	3.926 Inches Minimum And 3.956 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
End Item Identification:	F18 E/f
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	3.615 Inches Minimum And 3.635 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Criticality Code Justification:	Agav
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.798 Inches Minimum First Hole And 3.848 Inches Maximum First Hole
Part Name Assigned By Controlling Agency:	Bolt,close Tolerance, Hexagon Head,titanium,short Thread, .190 To .500
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V58D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.