

**Description**

Fastener Length: 3-61/64", Thread: 1/4-28, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS654V58D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-478-6425
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS654V58D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Left-hand
<b>Thread Length:</b>	0.316 Inches Nominal
<b>Fastener Length:</b>	3.926 Inches Minimum And 3.956 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Nominal
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
<b>End Item Identification:</b>	F18 E/f
<b>Nominal Thread Diameter:</b>	0.2500 Inches
<b>Grip Length:</b>	3.615 Inches Minimum And 3.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Agav
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	3.798 Inches Minimum First Hole And 3.848 Inches Maximum First Hole
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,close Tolerance, Hexagon Head,titanium,short Thread, .190 To .500
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams4928 Comp 6al-4v Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS654V58D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.