

**Description**

Fastener Length: 1-1/4", Thread: 5/16-24, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS655V14D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-514-1445
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS655V14D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.875 Inches Nominal
<b>Fastener Length:</b>	1.250 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Grip Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Single Shear Strength:</b>	7300 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.3125 Inches
<b>Grip Length:</b>	0.875 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Part Name Assigned By Controlling Agency:</b>	Navy Special Project
<b>Special Features:</b>	Item Has Drilled Shank
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Material Document And Classification:</b>	Nas621,comp 6al-4v Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas655 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS655V14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.