

Description

Fastener Length: 1-1/4", Thread: 5/16-24, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS655V14D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-514-1445
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS655V14D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Fastener Length:	1.250 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Single Shear Strength:	7300 Pounds Per Square Inch
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.875 Inches Nominal
Thread Quantity Per Inch:	24
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Special Features:	Item Has Drilled Shank
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Nas621,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas655 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS655V14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.