

Description

Fastener Length: 1-23/64", Thread: 3/8-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS656V12
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-915-4951
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS656V12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.391 Inches Nominal
Fastener Length:	1.314 Inches Minimum And 1.359 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.374 Inches Minimum And 0.375 Inches Maximum
Point Diameter:	0.374 Inches Nominal
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum Overall And 0.116 Inches Maximum Overall
Point Style:	Flat
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.745 Inches Minimum And 0.765 Inches Maximum
Thread Quantity Per Inch:	24
Material:	Titanium Alloy Uns R54520 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS656V12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.